

## RIBBED RUBBER MATTING

ISO/ASTM DESIGNATION = SBR

### Physical Characteristics:

Tensile: 435 PSI

Elongation: 300%

Hardness: 70 SHORE "A" +/-5

Temperature Range: -20°C to 80°C (-4°F to 176°F)



| Parts No.       | Ribbed | Gauge x Width | Length | Wt. Per LY | Colour |
|-----------------|--------|---------------|--------|------------|--------|
| RMBW-.125-24    | Wide   | 1/8" X 24"    | 25YDS  | 4.50       | Black  |
| RMBW-.125-36    | Wide   | 1/8" X 36"    | 25YDS  | 7.00       | Black  |
| RMBW-.125-36-50 | Wide   | 1/8" X 36"    | 50YDS  | 7.00       | Black  |
| RMBW-.125-48    | Wide   | 1/8" X 48"    | 25YDS  | 9.00       | Black  |
| RMGW-.125-36    | Wide   | 1/8" X 36"    | 25YDS  | 7.00       | Grey   |
| RMBRW-.125-36   | Wide   | 1/8" X 36"    | 25YDS  | 7.00       | Brown  |
| RMBW-.25-36     | Wide   | 1/4" X 36"    | 25YDS  | 14.00      | Black  |
| RMBW-.25-48     | Wide   | 1/4" x 48"    | 25YDS  | 18.50      | Black  |
| RMBF-.125-36    | Fine   | 1/8" X 36"    | 25YDS  | 7.00       | Black  |
| RMBF-.125-48    | Fine   | 1/8" X 48"    | 25YDS  | 9.00       | Black  |

**NOTE:** A low cost industrial commercial safety floor mat or runner available in customized widths to suit your toughest applications. The unique compound of polymer rich rubber provides outstanding wear resistance and durability for both indoor and outdoor environments.