



I.R.P. INDUSTRIAL RUBBER LTD.



IRP is Now a Full Line Stocking Distributor of



In Stock at IRP

SP Hose



Construction

Tube - yellow olefin
Reinforcement - single high tensile braid
Cover - orange polyether-urethane

Temperature Range

-40C to +50C (-40F to +122F)

Part Number	I.D. Inches	O.D. Inches	Max. W.P. PSI	Min. B.P. PSI	Min. Bend Radius	Cover Thickness	Approx. Wt. Per Ft. Lbs.	Reel Length Ft.
SP-16-500R	1	1.460	2500	6250	6	0.065	0.400	500
SP-16-600R	1	1.460	2500	6250	6	0.065	0.400	600

Each length comes with a male NPT attached each end; female swivel on one end is also available by special order.

HP Hose



Construction

Tube - yellow olefin
Reinforcement - double high tensile braid
Cover - blue polyether-urethane

Temperature Range

-40C to +50C (-40F to +122F)

Part Number	I.D. Inches	O.D. Inches	Max. W.P. PSI	Min. B.P. PSI	Min. Bend Radius	Cover Thickness	Approx. Wt. Per Ft. Lbs.	Reel Length Ft.
HP-16-600R	1	1.475	3000	7500	8	0.500	0.410	600

Each length comes with a male NPT attached each end; female swivel on one end is also available by special order.

The use of end fittings and assembly tooling other than that supplied by Piranha Hose Products is at the risk of the users.

6300 Edwards Blvd., Unit 1
Mississauga, ON L5T 2V7
Ph: 905-670-5700 / 1-800-387-9537
Fx: 905-670-3700
Email: sales@irprubber.com

1525 Broadway St., Unit 120
Port Coquitlam, BC V3C 6P6
Ph: 604-472-1200 / 1-877-527-1200
Fx: 604-472-1201
Email: saleswest@irprubber.com

Please visit our website at www.irprubber.com



Sewer Cleaning Hose