



CAY

## CONTRAMINE YELLOW AIR

### Application:

For mining, construction and industrial use where 300 PSI service is required. Mandrel built.

### Construction:

Tube - Synthetic oil mist resistant  
Reinforcement - Multiple layers of spiraled synthetic yarn  
Cover - Yellow cut and abrasion resistant rubber  
Branding - "300 PSI AIR HOSE"

### Temperature Range:

-40°C to +85°C (-40°F to +185°F)

### Standard Lengths:

25ft / 50ft / 75ft / 100ft

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
CAY-.5	1/2	0.91	300	0.25
CAY-.75	3/4	1.18	300	0.40
CAY-1	1	1.46	300	0.50
CAY-1.25	1-1/4	1.81	300	0.70
CAY-1.5	1-1/2	2.06	300	0.90
CAY-2	2	2.63	300	1.16
CAY-2.5	2-1/2	3.13	300	1.55
CAY-3	3	3.70	250	1.99
CAY-4	4	4.80	250	2.70



CAY400

## CONTRAMINE 400 AIR

### Application:

For mining, construction and industrial use where 400 PSI service is required. Mandrel built.

### Construction:

Tube - Synthetic oil mist resistant  
Reinforcement - Multiple layers of spiraled synthetic yarn  
Cover - Yellow cut and abrasion resistant rubber with black stripe  
Branding - Black Stripe "400 PSI AIR HOSE"

### Temperature Range:

-40°C to +85°C (-40°F to +185°F)

### Standard Lengths:

50ft / 100ft

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
CAY400-.5	1/2	0.91	400	0.25
CAY400-.75	3/4	1.18	400	0.40
CAY400-1	1	1.46	400	0.50