



WRY

STEEL MAXX

Application:

Extra high pressure air service for mining, construction and industrial use. Mandrel built.

Construction:

Tube - Black oil and heat resistant SBR/NBR rubber
 Reinforcement - Layers of high tensile steel wire
 Cover - Yellow, cut and gouge resistant synthetic rubber with red stripe
 Branding - Red Stripe "STEEL MAXX WIRE REINFORCED AIR"

Temperature Range:

-30°C to +80°C (-22°F to +176°F)

Standard Lengths:

50ft / 100ft

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
WRY-.5	1/2	0.98	600	0.44
WRY-.75	3/4	1.22	600	0.54
WRY-1	1	1.46	600	0.68
WRY-1.25	1-1/4	1.73	600	0.83
WRY-1.5	1-1/2	2.05	600	1.12
WRY-2	2	2.56	600	1.58
WRY-2.5	2-1/2	3.27	450	2.40
WRY-3	3	3.78	450	2.86
WRY-4	4	4.80	450	4.13



HERCULES

HERCULES 500

Application:

Hercules 500 is an extremely abrasion resistant hose with a wide range of applications in agriculture, factories, mining, and many other industrial applications. This hose is non-conductive and MSHA approved.

Construction:

Tube - NBR/PVC, RMA class A
 Reinforcement - 4-spiral polyester yarn
 Cover - NBR/PVC, carboxylated nitrile blend RMA class A, MSHA approved
 Branding - Thermoid Hercules Multipurpose Hose Size I.D. 500 PSI
 WP MSHA 1C-114/1 Made in USA Non-conductive

Temperature Range:

-40°C to +100°C (-40°F to +212°F)

Standard Lengths:

1/4" to 1" 25ft multiples & 700ft reels
 1-1/4" to 1-1/2" 25ft multiples & 500ft reels

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
HERCULES-.25	1/4	0.63	500	0.14
HERCULES-.375	3/8	0.75	500	0.21
HERCULES-.5	1/2	0.91	500	0.24
HERCULES-.75	3/4	1.19	500	0.36
HERCULES-1	1	1.50	500	0.51
HERCULES-1.25	1-1/4	1.75	500	0.66
HERCULES-1.5	1-1/2	2.09	500	0.70