



PSRKURI

PREMIUM POLYURETHANE SELF-RETRACTING AIR

Construction:

Transparent blue tint polyurethane, highly abrasion resistant and non-marking. Superior oil resistance, complies with RMA class A designation. Each length has 4" & 20" pigtails.

Temperature Range:

-18°C to +85°C (0°F to +150°F)

Note:

Self-retracting air hose fittings cannot be used on this hose. We recommend machined brass fittings attached with pinch clamps or ferrules. Working length is 80% of the nominal length described.

UNCOUPLED HOSE

Parts No.	I.D. Inches	O.D. Inches	Length Ft.	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
PSRKURI-.25-15	1/4	0.38	15	125	0.63
PSRKURI-.25-25	1/4	0.38	25	125	0.40
PSRKURI-.375-15	3/8	0.57	15	100	0.46
PSKKURI-.375-25	3/8	0.57	25	100	0.44

Other lengths available upon request



PSRKURI - COUPLED

COUPLED ASSEMBLIES WITH MALE SWIVELS EACH END

Parts No.	I.D. Inches	Length Extended ft.
PSRKURI-.25-MM-10	1/4	10
PSRKURI-.25-MM-15	1/4	15
PSRKURI-.25-MM-20	1/4	20
PSRKURI-.25-MM-25	1/4	25
PSRKURI-.25-MM-50	1/4	50
PSRKURI-.375-MM-10	3/8	10
PSRKURI-.375-MM-15	3/8	15
PSRKURI-.375-MM-20	3/8	20
PSKKURI-.375-MM-25	3/8	25
PSRKURI-.375-MM-50	3/8	50