



PU- COUPLED

## PREMIUM POLYURETHANE SELF-RETRACTING AIR

### Construction:

Blue polyurethane, highly abrasion resistant and non-marking. Superior oil resistance, complies with RMA class A designation. Each length has 4" & 20" pigtails.

### Temperature Range:

-18°C to +85°C (0°F to +150°F)

### Note:

Self-retracting air hose fittings cannot be used on this hose. Working length is 80% of the nominal length described.

### COUPLED ASSEMBLIES WITH MALE SWIVELS EACH END

Parts No.	I.D. Inches	Length Extended ft.
PUI4x10	1/4	10
PUI4x15	1/4	15
PUI4x20	1/4	20
PUI4x25	1/4	25
PUI4x50	1/4	50
PUI5x15	3/8	15
PUI5x20	3/8	20
PUI5x25	3/8	25
PUI5x50	3/8	50



CHAL-PU

## CHALLENGER COIL-MAXX POLYURETHANE SELF-RETRACTING AIR HOSE

### Application:

For assembly line air tools, work stations, and automotive repair.

### Construction:

Blue polyurethane, lightweight, highly abrasion resistant, and non-marking. Excellent memory, flexibility, and kink resistance. Each length has 4" and 20" pigtails.

### Packaging:

Poly bag labelled with ID and length

### Fittings:

Brass swivel fittings, complete with non-marking bend restrictors

### Temperature Range:

-18°C to +85°C (0°F to +185°F)

Parts No.	I.D. Inches	O.D. Inches	Max W.P. (PSI)	Length Extended ft.
CHAL-PU-.25-10	1/4	0.354	125	10
CHAL-PU-.25-15	1/4	0.354	125	15
CHAL-PU-.25-25	1/4	0.354	125	25
CHAL-PU-.25-50	1/4	0.354	125	50