



AH

## EPDM AUTO HEATER

### Application:

Standard duty heater hose.

### Construction:

Tube - Black heat and weather resistant EPDM rubber

Reinforcement - Two spirals of synthetic textile

Cover - Black heat resistant EPDM rubber. Resistant to anti-freeze solutions

### Temperature Range:

-40°C to +93°C (-40°F to +200°F)

### Standard Lengths:

25ft or 700ft reels

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Min. Burst PSI	Approx. Wt. Per. Ft. Lbs.
AH-.625	5/8	0.88	35	140	26
AH-.75	3/4	1.03	35	140	30
AH-1	1	1.34	25	100	40



AB

## AIR BRAKE

### Application:

For conveying air in truck and trailer brake systems. Meets D.O.T. FMVSS106-74, S.A.E. J-1402A and branded accordingly. Approved by the American Association of Motor Vehicle Administration.

### Construction:

Tube - EPDM rubber oil resistant

Reinforcement - Multi-spiral synthetic yarn

Cover - Black EPDM oil resistant resists abrasion, cracking and weather checking

### Temperature Range:

-40°C to +93°C (-40°F to +200°F)

### Standard Lengths:

25ft multiples or 700ft reels

Parts No.	I.D. Inches	O.D. Inches	Min. Burst PSI	Approx. Wt. Per. Ft. Lbs.
AB-.375	3/8	0.75	900	0.17
AB-.5	1/2	0.88	900	0.20