



TBOLTC

## CARBON STEEL T-BOLT CLAMPS

Carbon Steel T-Bolt clamps have a wide variety of uses such as hydraulic suction and discharge and suction hose assemblies. These clamps are used where gear clamps do not provide adequate strength. They have a large size range and are tightened with a standard socket wrench. The band has a beveled edge which helps to prevent damage to the hose cover when tightened.

**Please note:** Check the hose O.D. before ordering

Parts No.	Size Range Inches	
	From	To
TBOLTC- 17-19	22/32	24/32
TBOLTC- 20-22	25/32	28/32
TBOLTC- 23-25	29/32	1
TBOLTC- 26-28	1-1/32	1-3/32
TBOLTC- 29-31	1-5/32	1-7/32
TBOLTC- 32-35	1-9/32	1-12/32
TBOLTC- 36-39	1-13/32	1-17/32
TBOLTC- 40-43	1-18/32	1-22/32
TBOLTC- 44-47	1-23/32	1-27/32
TBOLTC- 48-51	1-28/32	2
TBOLTC- 52-55	2-2/32	2-5/32
TBOLTC- 56-59	2-7/32	2-10/32
TBOLTC- 60-63	2-11/32	2-15/32
TBOLTC- 64-67	2-17/32	2-20/32
TBOLTC- 68-73	2-22/32	2-28/32
TBOLTC- 74-79	2-29/32	3-3/32
TBOLTC- 80-85	3-5/32	3-10/32
TBOLTC- 86-91	3-12/32	3-18/32
TBOLTC- 92-97	3-20/32	3-26/32
TBOLTC- 98-103	3-27/32	4-2/32
TBOLTC- 104-112	4-3/32	4-12/32
TBOLTC- 113-121	4-14/32	4-24/32
TBOLTC- 122-130	4-25/32	5-4/32
TBOLTC- 131-139	5-4/32	5-16/32
TBOLTC- 140-148	5-16/32	5-28/32
TBOLTC- 149-161	5-28/32	6-12/32
TBOLTC- 162-174	6-12/32	6-28/32
TBOLTC- 175-187	6-28/32	7-12/32
TBOLTC- 188-200	7-12/32	7-28/32
TBOLTC- 201-213	7-28/32	8-12/32
TBOLTC- 214-226	8-12/32	8-28/32
TBOLTC- 227-239	8-28/32	9-12/32
TBOLTC- 240-252	9-12/32	9-28/32