



TBOLTS

STAINLESS STEEL T-BOLT CLAMPS - 302 S.S.

Stainless Steel T-Bolt clamps are used where there is risk of corrosion such as marine, coolant and food applications. These clamps are used where gear clamps do not provide adequate strength. They have a large size range and are tightened with a standard socket wrench. The band has a beveled edge which helps to prevent damage to the hose cover when tightened.

Please note: Check the hose O.D. before ordering.

Parts No.	Size Range Inches	
	From	To
TBOLTS- 17-19	22/32	24/32
TBOLTS- 20-22	25/32	28/32
TBOLTS- 23-25	29/32	1
TBOLTS- 26-28	1-1/32	1-3/32
TBOLTS- 29-31	1-5/32	1-7/32
TBOLTS- 32-35	1-9/32	1-12/32
TBOLTS- 36-39	1-13/32	1-17/32
TBOLTS- 40-43	1-18/32	1-22/32
TBOLTS- 44-47	1-23/32	1-27/32
TBOLTS- 48-51	1-28/32	2
TBOLTS- 52-55	2-2/32	2-5/32
TBOLTS- 56-59	2-7/32	2-10/32
TBOLTS- 60-63	2-11/32	2-15/32
TBOLTS- 64-67	2-17/32	2-20/32
TBOLTS- 68-73	2-22/32	2-28/32
TBOLTS- 74-79	2-29/32	3-3/32
TBOLTS- 80-85	3-5/32	3-10/32
TBOLTS- 86-91	3-12/32	3-18/32
TBOLTS- 92-97	3-20/32	3-26/32
TBOLTS- 98-103	3-27/32	4-2/32
TBOLTS- 104-112	4-3/32	4-12/32
TBOLTS- 113-121	4-14/32	4-24/32
TBOLTS- 122-130	4-25/32	5-4/32
TBOLTS- 131-139	5-5/32	5-15/32
TBOLTS- 140-148	5-16/32	5-26/32
TBOLTS- 149-161	5-28/32	6-11/32
TBOLTS- 162-174	6-12/32	6-27/32
TBOLTS- 227-239	8-30/32	9-13/32