



FLX-BMD

FLX-THANE MD POLYURETHANE

Colour:

Black

Temperature Range:

-54°C to +107°C (+65°F to +225°F)

Stock Sizes:

2"-12"

Available Sizes:

2"-24"

Standard Stock Sizes:

25ft only

Non Standard Lengths:

Made to order

FLX-THANE MD - Durable urethane hose has excellent resistance to abrasion, cutting and gouging for a long product life. It is reinforced with a bronze coated spring steel helix, it maintains its excellent flexing characteristics even in the roughest conditions. The ideal hose for lightweight materials handling.

Wall Thickness= .030"

Parts No.	I.D. Inches	Weight (lbs./ft.)	Positive Pressure PSI	Negative Pressure IN.HG	Centerline Bend Radius, Inches
FLX-BMD-2	2	.25	30	29.0	2.00
FLX-BMD-2.5	2-1/2	.32	30	29.0	2.50
FLX-BMD-3	3	.40	29	29.0	3.00
FLX-BMD-3.5	3-1/2	.52	28	22.0	3.50
FLX-BMD-4	4	.70	25	29.0	4.00
FLX-BMD-5	5	.90	22	17.0	5.00
FLX-BMD-6	6	1.00	19	15.0	6.00
FLX-BMD-7	7	1.20	16	12.0	7.00
FLX-BMD-8	8	1.50	14	9.0	8.00
FLX-BMD-9	9	1.55	12	5.0	9.00
FLX-BMD-10	10	1.60	11	4.0	8.00
FLX-BMD-12	12	2.00	10	2.2	10.00
FLX-BMD-14	14	2.50	8	3.3	12.00
FLX-BMD-16	16	3.00	7	2.2	14.00
FLX-BMD-18	18	3.30	6	1.40	16.00

*Pressures based on straight lengths of hose @ 72° F.