



FLX-VHD

FLX-THANE VHD POLYURETHANE

Colour:

Clear

Temperature Range:

-54°C to +107°C (-65°F to +225°F)

Stock Sizes:

None

Available Sizes:

4" - 24"

Standard Stock Sizes:

25ft only

Non Standard Lengths:

Made to order

FLX-THANE VHD - A very heavy weight polyurethane hose reinforced with a spring steel coated wire helix (sizes 14" and above not available with a coated wire) Great abrasion resistance and high tear strength. Ideal for severe service applications where flexibility is required. Clear is manufactured with FDA acceptable materials.

Wall Thickness = .045" - 2" to 3.5"
.060" - 4" and above

Parts No.	I.D. Inches	Weight (lbs./ft.)	Positive Pressure PSI	Negative Pressure IN.HG	Centerline Bend Radius, Inches
FLX-VHD-4	4	1.00	34	29	4
FLX-VHD-5	5	1.30	33	17	5
FLX-VHD-6	6	1.50	32	15	6
FLX-VHD-8	8	1.90	29	9	8
FLX-VHD-10	10	2.20	25	4	10
FLX-VHD-12	12	2.60	20	2.5	12
FLX-VHD-14	14	3.80	18	3.5	14
FLX-VHD-16	16	4.20	15	2.5	16
FLX-VHD-18	18	4.80	12	1.5	18

*Pressures based on straight lengths of hose @ 72° F.