



CW-GP

## CW-GP DOUBLE PLY NEOPRENE / POLYESTER

### Colour:

Black

### Temperature Range:

-40°C to +121°C (+40°F to +250°F)

### Stock Sizes:

1"-24"

### Available Sizes:

1"-48"

### Standard Stock Sizes:

1"-12" 25 & 50ft only

14"-24" 25ft only

### Non Standard Lengths:

Multiples of 5ft

**CW-GP** - Double ply neoprene impregnated polyester fabric hose construction, reinforced with a spring steel wire helix. It has excellent crush resistance and tensile strength. The neoprene coating offers excellent abrasion and chemical resistance. Handles positive and negative pressure and is extremely flexible. More durable than double ply cotton hose. CW-GP is UL 94V-0 flame retardant.

Parts No.	I.D. Inches	Weight (lbs./ft.)	Positive Pressure PSI	Negative Pressure IN.HG	Centerline Bend Radius, Inches
CW-GP-2	2	.25	30	29.0	1.70
CW-GP-2.5	2-1/2	.289	30	29.0	1.80
CW-GP-3	3	.35	30	29.0	2.40
CW-GP-3.5	3-1/2	.40	30	29.0	2.50
CW-GP-4	4	.57	30	29.0	3.10
CW-GP-5	5	.70	17	17.0	3.50
CW-GP-6	6	.95	11	22.0	4.54
CW-GP-7	7	1.02	22	11.0	5.00
CW-GP-8	8	1.09	6.5	7.3	5.50
CW-GP-9	9	1.23	5	5.0	5.50
CW-GP-10	10	1.36	5	5.0	6.90
CW-GP-12	12	1.62	4.3	3.8	2.70
CW-GP-14	14	2.60	3.7	3.7	10.00
CW-GP-16	16	2.90	3.2	2.5	12.00
CW-GP-18	18	3.30	3	1.8	13.00

\*Pressures based on straight lengths of hose @ 72° F.