

Flexaust Hose & Ducting

Flexaust Hose & Ducting



CWS SINGLE PLY NEOPRENE / POLYESTER

Colour:

Black

Temperature Range:

-54°C to +121°C (-65°F to +250°F)

Stock Sizes:

2"-12"

Available Sizes:

2"-12"

Standard Stock Sizes:

10/15/25ft only

Non Standard Lengths:

Made to order

CWS - Single ply neoprene/polyester construction offers exceptional flexibility and retractability. Recommended for less demanding low pressure air handling, fume control and dust collection applications. Spring steel wire helix for good crush resistance. CWS is flame retardant to UL 94V-0.

Parts No.	I.D. Inches	Weight (lbs./ft.)	Positive Pressure PSI	Negative Pressure IN.HG	Centerline Bend Radius, Inches
CWS-R-2	2	.24	30	29	1.80
CWS-R-2.5	2-1/2	.25	30	29	2.00
CWS-R-3	3	.36	30	29	2.50
CWS-R-4	4	.47	18	29	3.00
CWS-R-5	5	.59	15	17	3.50
CWS-R-6	6	.67	7	16	4.00
CWS-R-7	7	.83	6	15	5.00
CWS-R-8	8	.90	5	10	5.50
CWS-R-10	10	1.10	4	4	6.00
CWS-R-12	12	1.40	3	3	7.00

*Pressures based on straight lengths of hose @ 72° F.

