

Flexaust Hose & Ducting

Flexaust Hose & Ducting



FSP-2

FSP-2 DOUBLE PLY PVC / POLYESTER

Colour:

Black

Temperature Range:

-29°C to +82°C (-20°F to +180°F)

Stock Sizes:

3"-12"

Available Sizes:

3"-12"

Standard Stock Sizes:

25ft only

Non Standard Lengths:

Made to order

FSP-2 - A double ply flame retardant PVC coated polyester fabric construction with an enclosed spring steel wire helix & external PVC wearstrip. FSP-2 offers superior chemical resistance, low friction loss and is flame retardant to UL 94V-0.

Parts No.	I.D. Inches	Weight (lbs./ft.)	Positive Pressure PSI	Negative Pressure IN.HG	Centerline Bend Radius, Inches
FSP-2-3	3	.50	13	29	2.80
FSP-2-4	4	.72	10	24	3.70
FSP-2-5	5	.89	8	13	4.70
FSP-2-6	6	1.06	7	7.3	5.30
FSP-2-7	7	1.24	6	5	6.50
FSP-2-8	8	1.48	4	7	6.90
FSP-2-10	10	1.84	3	3.7	8.60
FSP-2-12	12	2.20	2.6	2.2	10.00

*Pressures based on straight lengths of hose @ 72° F.