

Flexaust Hose & Ducting

Flexaust Hose & Ducting



COMMERCIAL

COMMERCIAL POLYETHYLENE COPOLYMER

Colour:

Grey or Black

Temperature Range:

-40°C to +60°C (+40°F to +140°F)

Stock Sizes:

1-1/4" - 4"

Available Sizes:

1-1/4" - 4"

Standard Stock Sizes:

25 & 50ft only

Non Standard Lengths:

Made to order

COMMERCIAL VACUUM HOSE - Constructed of grey or black polyethylene copolymer hose reinforced with an integral polyethylene helix. The unique design provides exceptional abrasion resistance without sacrificing flexibility. The smooth interior and exterior allows for easy handling, storage and high flow rates.

Parts No.	I.D. Inches	Colour	Weight (lbs./ft.)	Positive Pressure PSI	Negative Pressure IN.HG	Centerline Bend Radius, Inches
IH-WWG-1.25	1-1/4	GREY	.20	20	29	2.40
IH-RX-1.25	1-1/4	BLACK	.20	20	29	2.40
IH-WWG-1.5	1-1/2	GREY	.28	16	29	2.75
IH-RX-1.5	1-1/2	BLACK	.28	16	29	2.75
IH-WWG-2	2	GREY	.42	15	29	4.25
IH-RX-2	2	BLACK	.42	15	29	4.25
IH-WWG-2.5	2-1/2	GREY	.53	14	29	5.00
IH-RX-2.5	2-1/2	BLACK	.53	14	29	5.00
IH-WWG-3	3	GREY	.65	9	29	7.50
IH-RX-3	3	BLACK	.65	9	29	7.50
IH-WWG-4	4	GREY	1.00	8	29	9.50
IH-RX-4	4	BLACK	1.00	8	29	9.50

*Pressures based on straight lengths of hose @ 72° F.

ACCESSORIES FOR COMMERCIAL POLYETHYLENE COPOLYMER

Screw on standard cuffs

Parts No.	I.D. Inches
IHCUFFG-1.25	1-1/4
IHCUFFG-1.5	1-1/2
IHCUFFG-2	2

Screw on nozzle-grey standard

Parts No.	I.D. Inches
IHNOZ-1.5	1-1/2
IHNOZ-2	2

