

Flexaust Hose & Ducting

Flexaust Hose & Ducting

B-A



BENDWAY (Aluminum)

Temperature Range:

-73°C to +204°C (+100°F to +400°F)

Stock Sizes:

2" - 12"

Available Sizes:

2" - 12"

Standard Stock Sizes:

10ft only

Non Standard Lengths:

None

BENDWAY - Single ply helically corrugated aluminum alloy hose with a four-ply finished seam that is folded flat and crimped for tightness and strength. Light-weight and hand bendable allowing for elbows and turns to be formed easily during installation. Bendway's self-supporting construction allows for bends to stay in place. Resists metal fatigue, weathering, and most corrosive fumes and chemicals.

Wall Thickness = .008"

Parts No.	I.D. Inches	Weight (lbs./ft.)	Positive Pressure PSI	Negative Pressure IN.HG	Centerline Bend Radius, Inches
B-A-2	2	.113	N/A	N/A	4.00
B-A-3	3	.167	N/A	N/A	5.70
B-A-4	4	.20	N/A	N/A	7.50
B-A-5	5	.25	N/A	N/A	9.30
B-A-6	6	.30	N/A	N/A	11.20
B-A-7	7	.35	N/A	N/A	13.00
B-A-8	8	.35	N/A	N/A	15.00
B-A-9	9	.40	N/A	N/A	17.00
B-A-10	10	.44	N/A	N/A	19.00
B-A-12	12	.53	N/A	N/A	23.00

*Pressures based on straight lengths of hose @ 72° F.