

Flexaust Hose & Ducting



S-SDW

SD-W SINGLE PLY NEOPRENE / POLYESTER

Colour:

Yellow with black wearstrip

Temperature Range:

-54°C to +121°C (+65°F to +250°F)

Retractability:

6 TO 1

Stock Sizes:

4"- 18"

Available Sizes:

4"- 18"

Standard Stock Sizes:

25ft only

Non Standard Lengths:

Made to order

SDW - Springflex duct type SDW provides superior performance when it comes to moving large volumes of air. Extremely flexible and lightweight. SDW easily compresses for storage, making it the ideal duct for use with both portable and permanent ventilation and exhaust systems. Type SDW is constructed of single ply heavyweight neoprene impregnated polyester fabric supported by a fully enclosed spring steel wire helix. Flame retardant to UL 94V-0. SDW comes with the addition of an external wearstrip for added external abrasion resistance.

Parts No.	I.D. Inches	Weight (lbs./ft.)	Positive Pressure PSI	Centerline Bend Radius, Inches
S-SDW-4	4	.25	5.40	3.00
S-SDW-5	5	.27	3.00	3.50
S-SDW-6	6	.30	3.00	3.50
S-SDW-7	7	.38	3.00	4.50
S-SDW-8	8	.40	3.00	5.00
S-SDW-9	9	.50	2.50	6.20
S-SDW-10	10	.60	2.50	6.50
S-SDW-12	12	.70	2.00	7.50
S-SDW-14	14	.80	1.70	8.50
S-SDW-16	16	.90	1.50	9.50
S-SDW-18	18	1.00	1.30	10.50
S-SDW-20	20	1.10	1.10	12.00
S-SDW-22	22	1.40	1.05	12.50
S-SDW-24	24	1.60	1.00	13.00

*Available without external wearstrip - (SD)

Parts No.	I.D. Inches	Weight (lbs./ft.)	Positive Pressure PSI	Centerline Bend Radius, Inches
S-SD-4	4	.25	5.40	3.00
S-SD-5	5	.30	3.00	3.50
S-SD-6	6	.30	3.00	3.50
S-SD-7	7	.35	3.00	4.00
S-SD-8	8	.40	3.00	5.00
S-SD-9	9	.50	2.50	6.00
S-SD-10	10	.60	2.50	6.50
S-SD-12	12	.70	2.00	7.50
S-SD-14	14	.80	1.70	8.50
S-SD-16	16	.90	1.50	9.50
S-SD-18	18	1.00	1.30	10.50
S-SD-20	20	1.10	1.10	12.00
S-SD-22	22	1.40	1.05	12.50
S-SD-24	24	1.60	1.00	13.00

*Pressures based on straight lengths of hose @ 72° F.

