



TIGER

## TIGER TAIL

### Colour:

Yellow / Black

### Temperature Range:

-54°C to +107°C (-40°F to +140°F)

### Stock Sizes:

None

### Available Sizes:

1-1/4", 2", 3", 4"

### Standard Stock Sizes:

25 & 50ft only

### Non Standard Lengths:

Made to order

**TIGER TAIL** - Improved double helix design allows for superior flexibility and durability even in sub-zero temperatures. Designed to provide maximum abrasion protection for sewer jetting hose, expensive camera and utility inspection equipment. Has superior abrasion and crush resistance and is resistant to kinking. Made with factory installed leak proof polyweld cuffs. Adaptable to eye hoods, D-rings, clamps and other guide rope attachment methods.

Parts No.	I.D. Inches	Weight (lbs./ft.)	Positive Pressure PSI	Negative Pressure IN.HG	Centerline Bend Radius, Inches
TIGER-1.5	1-1/2	.35	26	29	3.75
TIGER-2	2	.65	17	29	5.00
TIGER-3	3	1.20	12	29	8.00
TIGER-4	4	1.60	7	29	9.50

\*Pressures based on straight lengths of hose @ 72° F.



BCCW

## FLEXAUST BRIDGE CLAMPS

Parts No.	Size Inches	Spiral Direction
BCCW-3	3	Clockwise
BCCW-4	4	Clockwise
BCCW-5	5	Clockwise
BCCW-6	6	Clockwise
BCCW-8	8	Clockwise
BCCW-10	10	Clockwise
BCCW-12	12	Clockwise
BCCC-3	3	Counter Clockwise
BCCC-4	4	Counter Clockwise
BCCC-5	5	Counter Clockwise
BCCC-6	6	Counter Clockwise
BCCC-8	8	Counter Clockwise
BCCC-10	10	Counter Clockwise
BCCC-12	12	Counter Clockwise

**NOTE:** Bridge clamps are available in clockwise for Flexaust hose and counter clockwise for Flex-Lok hose.