

Food Handling Hose



WF

FOOD MAXX

Application:

For handling most liquid food products including fats and oils without imparting taste, odour, or smell. Suitable for full vacuum service.

Construction:

Tube - White nitrile, non-toxic, FDA approved
Reinforcement - A steel helix embedded between layers of synthetic cords
Cover - Grey nitrile rubber
Branding - Red Stripe "FOOD MAXX FDA FOOD SUCTION 250 P.S.I."

Temperature Range:

-35°C to +93°C (-31°F to +200°F)

Standard Lengths:

50ft / 100ft

Parts No.	I.D. Inches	O.D. Inches	Bend Radius Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
WF-1.5	1-1/2	2.00	12	250	1.25
WF-2	2	2.60	16	250	1.86
WF-2.5	2-1/2	3.10	20	250	2.41
WF-3	3	3.60	24	250	2.83
WF-4	4	4.70	32	250	4.10



MH

PVC MILK

Application:

Designed to handle milk in all applications from pick-up to processing plant. This hose is extremely flexible. Suitable for full vacuum. Meets FDA and 3A requirements

Construction:

Tube - Smooth, clear FDA and 3A approved PVC
Reinforcement - PVC helix FDA and 3A approved
Cover - Smooth, clear FDA and 3A approved PVC

Temperature Range:

-25°C to +70°C (-13°F to +158°F)

Standard Lengths:

50ft / 100ft

Parts No.	I.D. Inches	O.D. Inches	Bend Radius Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
MH-1.5	1-1/2	1.82	2.0	66	0.44
MH-2	2	2.39	2.5	66	0.74