

Food Handling Hose

Food Handling Hose



PVCTUB

CLEAR PVC TUBING - FOOD GRADE

Application:

For handling beverages, food stuffs and liquids where clarity, flexibility and a food grade compound are required. This product complies with all applicable FDA, 3A, NSF-51 and NSF-61 requirements.

Construction:

Tube - Crystal clear non-toxic, odourless and taste free PVC compound manufactured in compliance with applicable FDA, 3A, NSF-51 and NSF-61 requirements

Cover - Food grade crystal clear PVC

Temperature Range:

-4°C to +65°C (+25°F to +150°F)

Standard Lengths:

1/8" to 1" 100ft

1-1/4" to 2" 50ft

Parts No.	I.D. Inches	O.D. Inches	Wall Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
PVCTUB-.125	1/8	1/4	1/16	65	.020
PVCTUB-.188-.25	3/16	1/4	1/32	50	.012
PVCTUB-.188	3/16	5/16	1/16	55	.027
PVCTUB-.25-.375	1/4	3/8	1/16	55	.034
PVCTUB-.25-5	1/4	1/2	1/8	60	.080
PVCTUB-.313	5/16	7/16	1/16	50	.040
PVCTUB-.375-.5	3/8	1/2	1/16	45	.047
PVCTUB-.375-.625	3/8	5/8	1/8	55	.107
PVCTUB-.5-.625	1/2	5/8	1/8	30	.060
PVCTUB-.5-.75	1/2	3/4	1/8	45	.134
PVCTUB-.625-.75	5/8	3/4	1/16	30	.082
PVCTUB-.625	5/8	7/8	1/8	40	.161
PVCTUB-.75	3/4	1	1/8	35	.188
PVCTUB-.875	7/8	1-1/8	1/8	30	.214
PVCTUB-1	1	1-1/4	1/8	25	.241
PVCTUB-1-1.5	1	1-1/2	1/4	35	.536
PVCTUB-1.25	1-1/4	1-1/2	1/8	20	.296
PVCTUB-1.5	1-1/2	1-7/8	3/16	30	.542
PVCTUB-1.5-2	1-1/2	2	1/4	35	.750
PVCTUB-2	2	2-1/2	1/4	35	.964



POLY

POLYETHYLENE TUBING - FOOD GRADE

Application:

Used as instrumentation tubing and as transmission lines for air, liquids and gases. Non corrosive, odourless and tasteless. Milky white colour. Food grade.

Construction:

Low density extruded polyethylene tubing is manufactured from top quality virgin resins, is free from impurities and offers excellent resistance to stress cracking. Food grade.

Temperature Range:

-45°C to +60°C (-50°F to +140°F)

Parts No.	I.D. Inches	O.D. Inches	Wall Inches	STD Lengths FT.	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
POLY-.125	1/8	1/4	0.062	2000	150	0.015
POLY-.170	.170	1/4	0.040	2000	140	0.011
POLY-.188	3/16	5/16	0.062	1500	150	0.020
POLY-.25	1/4	3/8	0.062	1000	125	0.025
POLY-.375	3/8	1/2	0.062	500	100	0.035
POLY-.5	1/2	5/8	0.062	500	75	0.045

