

Garage Exhaust Hose

Garage Exhaust Hose



FLT

FLARELOCK HOSE

Product Information:

A crush resistant heavy duty exhaust hose made of specially compound rubber to resist heat, aging, gasoline, exhaust fumes and oil. Individual lengths are easily interconnected. When using on vehicles with catalytic mufflers, temperatures can be as high as 600°F. In these applications, use metal transitions to lower exhaust temperatures to acceptable levels.

Standard Lengths:

2" to 4" 11ft

Parts No.	I.D. Inches	Heat Resistance	Approx. Wt. Per. Length Lbs.
FLT200	2	400°F (600°F Intermittent)	6.2
FLT250	2-1/2	400°F (600°F Intermittent)	7.0
FLT300	3	400°F (600°F Intermittent)	9.4
FLT400	4	400°F (600°F Intermittent)	16.0

* This hose is to be used only when there is no load on engine.



ACT

ACT HOSE

Product Information:

Designed use with larger gas vehicles and diesel trucks. Act hose is formulated from same high temperature rubber as Flarelock hose. The main difference being, a splice connector must be used when joining two lengths of Act hose together.

Standard Lengths:

5" to 6" 11ft

Parts No.	I.D. Inches	Heat Resistance	Approx. Wt. Per. Length Lbs.
ACT500	5	400°F (600°F Intermittent)	24.53
ACT600	6	400°F (600°F Intermittent)	25.96