

General Purpose Hose

General Purpose Hose



CHAL

CHALLENGER EPDM GENERAL SERVICE HOSE

Application:

An economical EPDM multi purpose hose used in a wide range of air, water, and light agricultural chemical applications. Challenger General Service hose is used in construction, marine, agricultural, and industrial applications.

Construction:

Tube - Black EPDM blended rubber
Reinforcement - Polyester yarn
Cover - Smooth red abrasion resistant EPDM blend

Temperature Range:

-20°C to +93°C (-4°F to +200°F)

Standard Lengths:

25ft multiples & 500ft reels

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
CHAL-.25-250	1/4	0.51	250	0.11
CHAL-.375-250	3/8	0.67	250	0.16
CHAL-.5-250	1/2	0.83	250	0.23
CHAL-.75-250	3/4	1.14	250	0.40
CHAL-1-200	1	1.40	200	0.53



TUNDRA

TUNDRA LOW TEMP PVC AIR HOSE

Application:

Tundra is an ideal hose for outdoor air and water applications in cold weather. Its specially formulated compounds are engineered to be tough and flexible at very low temperatures. Tundra is also silicone free.

Construction:

Tube- High grade low temp. PVC compound. Medium Class B oil resistance
Reinforcement- High tensile strength polyester yarn
Cover- High grade low temp. PVC compound. Medium Class B oil resistance

Temperature Range:

-40°C to +65°C (-40°F to +150°F)

Standard Lengths:

1/4" to 1/2" - 500ft reel no cutting
Full coils / reels only.

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
TUNDRA-RED-.25	1/4	0.50	300	0.08
TUNDRA-RED-.375	3/8	0.63	300	0.10
TUNDRA-YEL-.375-500R	3/8	0.63	300	0.10
TUNDRA-YEL-.5-500R	1/2	0.78	300	0.15

