

General Purpose Hose

General Purpose Hose



HERCULES

HERCULES 500

Application:

Hercules 500 is an extremely abrasion resistant hose with a wide range of applications in agriculture, factories, mining, and many other industrial applications. This hose is non-conductive and MSHA approved.

Construction:

Tube – NBR/PVC, RMA class A

Reinforcement – 4-spiral polyester yarn

Cover – NBR/PVC, carboxylated nitrile blend RMA class A, MSHA approved

Branding - Thermoid Hercules Multipurpose Hose Size I.D. 500 PSI
WP MSHA 1C-114/1 Made in USA Non-conductive

Temperature Range:

-40°C to +100°C (-40°F to +212°F)

Standard Lengths:

1/4" to 1" 25ft multiples & 700ft reels

1-1/4" to 1-1/2" 25ft multiples & 500ft reels

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
HERCULES-.25	1/4	0.63	500	0.14
HERCULES-.375	3/8	0.75	500	0.21
HERCULES-.5	1/2	0.91	500	0.24
HERCULES-.75	3/4	1.19	500	0.36
HERCULES-1	1	1.50	500	0.51
HERCULES-1.25	1-1/4	1.75	500	0.66
HERCULES-1.5	1-1/2	2.09	500	0.70