

Material Handling Hose



BMS

BULKMASTER DISCHARGE

Application:

For discharge of dry bulk products including chalk, china clay, limestone, ground silica, fullers earth, dry cement, sodium sulphate, lime and fertilizer.

Construction:

Tube - Black abrasion resistant natural rubber
Reinforcement - Spiraled layers of high tensile synthetic cord
Cover - Black abrasion and weather resistant synthetic rubber
Branding - Green Stripe "Bulkmaster Discharge"

Temperature Range:

-35°C to +82°C (-31°F to +180°F)

Standard Lengths:

100ft cut to multiples of 5ft

Parts No.	I.D. Inches	O.D. Inches	Tube Gauge Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
BMS-3	3	3.70	3/16	80	1.87
BMS-4-.125	4	4.54	1/8	75	2.02
BMS-4-.188	4	4.54	3/16	75	2.20
BMS-4-.25	4	4.72	1/4	75	2.76
BMS-4-.313	4	4.69	5/16	75	2.90
BMS-4.5	4-1/2	5.22	1/4	75	2.97



BH

BULKMASTER HARDWALL

Application:

For suction and discharge of dry bulk products including chalk, china clay, limestone, ground silica, fullers earth, dry cement, sodium sulphate, lime and fertilizer. Suitable for full vacuum.

Construction:

Tube - Black abrasion resistant natural rubber
Reinforcement - A high tensile steel helix embedded between textile cords.
Cover - Black abrasion and weather resistant synthetic rubber with white stripe
Branding - Green Stripe "Bulkmaster Suction"

Temperature Range:

-35°C to +82°C (-31°F to +180°F)

Standard Lengths:

100ft cut to multiples of 5ft

Parts No.	I.D. Inches	O.D. Inches	Bend Radius Inches	Tube Gauge Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
BH-4-.188	4	4.80	35	3/16	75	3.85
BH-4-.25	4	4.94	35	1/4	75	4.41
BH-4-.313	4	5.08	35	5/16	75	4.96