

Material Handling Hose

Material Handling Hose



SB

BLAST MAXX

Application:

For conducting sand, steel shot and other abrasives for blast cleaning.

Construction:

Tube - 1/4" black static conductive abrasion resistant natural rubber
Reinforcement - Two layers of synthetic textile cords
Cover - Black natural / EPDM blended rubber
Branding - Red Stripe "BLAST MAXX SANDBLAST HOSE 150 P.S.I."

Temperature Range:

-35°C to +82°C (-31°F to +180°F)

Standard Lengths:

50ft / 100ft

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
SB-.5-1.063	1/2	1.063	150	0.47
SB-.5-1.125	1/2	1.125	150	0.49
SB-.75-1.5	3/4	1.500	150	0.72
SB-1	1	1.875	150	1.06
SB-1.25-1.875	1-1/4	1.875	150	1.11
SB-1.25-2.156	1-1/4	2.156	150	1.25
SB-1.5	1-1/2	2.375	150	1.43
SB-2	2	2.875	150	1.69
SB-2.5	2-1/2	3.425	150	2.37
SB-3	3	4.000	150	3.09



CP

CONCRETE PLACEMENT

Application:

For conducting plaster, grout, wet cement and concrete at high pressure

Construction:

Tube - Black abrasion resistant natural rubber
Reinforcement - Layers of high tensile synthetic cords
Cover - Black abrasion resistant synthetic rubber
Branding - White Stripe

Temperature Range:

-35°C to +82°C (-31°F to +180°F)

Standard Lengths:

50ft / 100ft

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
CP-1.5	1-1/2	2.25	800	1.19
CP-2	2	2.76	800	1.29
CP-3	3	4.00	800	2.54
CP-4	4	5.12	600	3.85

