

Material Handling Hose



TB

BULK MAXX

Application:

For transfer of dry non-oily abrasive materials such as sand, limestone, plastic pellets, sugar, corn etc. Suitable for full vacuum.

Construction:

Tube - Tan natural rubber smooth abrasion resistant, 3/16" thick (FDA approved)
 Reinforcement - A high tensile steel helix embedded between textile cords
 Cover - Tan natural rubber corrugated for flexibility, non marking
 Branding - Blue Stripe "BULK MAXX TAN BULK MATERIAL"

Temperature Range:

-35°C to +82°C (-31°F to +180°F)

Standard Lengths:

2" to 4" 100ft multiples of 5ft
 5" to 6" 60ft multiples of 5ft

Parts No.	I.D. Inches	O.D. Inches	Bend Radius Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
TB-2	2	2.64	10	75	1.68
TB-2.5	2-1/2	3.11	14	75	2.24
TB-3	3	3.66	16	75	2.74
TB-4	4	4.69	22	75	3.56
TB-5	5	5.71	32	75	4.56
TB-6	6	6.73	37	75	5.40

INDUSTRIAL VACUUM - WITH PURE GUM TUBE

Application:

A rugged flexible heavy duty vacuum cleaning hose designed for demanding industrial use.

Construction:

Tube - Tan abrasion resistant Pure Gum
 Reinforcement - Two high tensile steel wire helices and spirals of synthetic yarn
 Cover - Black corrugated abrasion resistant SBR Rubber
 Branding - Unbranded

Temperature Range:

-35°C to +82°C (-31°F to +180°F)

Standard Lengths:

1" - 4" 100ft cut to multiples of 10ft
 5" & 6" 60ft cut to multiples of 10ft
 8" 40ft cut to multiples of 10ft



IV

Parts No.	I.D. Inches	O.D. Inches	Bend Radius Inches	Tube Gauge Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
IV-1	1	1.25	6	3/64	200	0.33
IV-1.25	1-1/4	1.50	8	3/64	200	0.45
IV-1.5	1-1/2	1.75	9	3/64	180	0.53
IV-2	2	2.32	12	3/64	140	0.81
IV-2.5	2-1/2	2.80	15	3/64	110	1.00
IV-3	3	3.31	18	3/64	90	1.27
IV-4	4	4.41	24	3/64	70	2.05
IV-5	5	5.39	30	3/64	80	2.91
IV-6	6	6.46	36	3/64	70	4.81
IV-8	8	8.45	46	3/64	50	6.90

