

# Material Handling Hose



180BL

## 180BL ABRASION RESISTANCE RUBBER SUCTION

### Application:

Designed for suction and blowing of lightweight abrasives such as rock-wool, fiberglass, sawdust, grain, insulation and cement dust.

### Construction:

Tube- SBR rubber blended with static carbon black. Smooth bore  
Reinforcement- Rigid PVC helix  
Cover- SBR Rubber blended with static carbon black. Corrugated cover

### Temperature Range:

-40°C to +60°C (-40°F to +140°F)

### Standard Lengths:

2-1/2" - 100ft no cutting  
3" to 6" - 100ft/50ft no cutting

Parts No.	I.D. Inches	O.D. Inches	Vacuum Rating (In. Hg) 68F	Bend Radius Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
180BL-2.5	2-1/2	2.91	25	2.5	18	0.71
180BL-3	3	3.44	23	3	13	0.92
180BL-4	4	4.53	20	4	10	1.50
180BL-5	5	5.63	15	5	8	1.68
180BL-6	6	6.67	15	9	8	2.40



620WD

## KANAFLEX 620WD BLOWER HOSE

### Application:

General ducting and blower applications. For use with lightweight abrasives such as sawdust, grass clippings, street refuse and cotton pickers.

### Construction:

Tube- Smooth EPDM  
Reinforcement- Metal wire helix  
Cover- Slightly corrugated EPDM Rubber

### Temperature Range:

-40°C to +104°C (-40°F to +220°F)

### Standard Lengths:

2-1/2" to 10ft - 50ft no cutting  
12" - 25ft no cutting

Parts No.	I.D. Inches	O.D. Inches	Vacuum Rating (In. Hg) 68F	Bend Radius Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
620WD-2.5	2-1/2	3.00	12	3	12	0.44
620WD-4	4	4.39	9	4	9	0.73
620WD-6	6	6.36	6	6	6	1.04
620WD-8	8	8.35	4	8	4	1.38
620WD-10	10	10.45	3	10	3	2.40
620WD-12	12	12.40	3	12	3	2.50