

# Petroleum Hose



TT

## PETRO MAXX

### Application:

An all purpose suction and discharge hose for gasoline, distillate, kerosene, diesel, oil suspensions and emulsions. Also used as hydraulic return line suction hose. Suitable for full vacuum. Maximum aromatic content 50%.

### Construction:

Tube - Black Nitrile for maximum oil resistance

Reinforcement - A high tensile wire helix embedded between layers of textile cords

Cover - Black abrasion resistant PVC nitrile blend which is gasoline and oil resistant c/w a blue layline

Branding - Blue stripe "PETRO MAXX TANK TRUCK 150 PSI"

### Temperature Range:

-35°C to +82°C (-31°F to +180°F)

### Standard Lengths:

100ft cut to multiples of 5ft

Parts No.	I.D. Inches	O.D. Inches	Bend Radius Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
TT-.75	3/4	1.19	5	150	0.45
TT-1	1	1.42	6	150	0.58
TT-1.25	1-1/4	1.70	7	150	0.78
TT-1.5	1-1/2	1.97	9	150	0.89
TT-2	2	2.48	12	150	1.15
TT-2.5	2-1/2	2.95	20	150	1.40
TT-3	3	3.53	24	150	1.92
TT-3.5	3-1/2	4.06	28	150	2.37
TT-4	4	4.75	32	100	3.20
TT-5	5	5.79	40	100	5.73
TT-6	6	6.85	48	100	5.89



TT-LT

## POLAR MAXX LOW TEMP TANK TRUCK

### Application:

An all purpose petroleum suction and discharge hose designed to remain flexible under arctic service conditions. Suitable for full vacuum.

### Construction:

Tube - Black low temp nitrile for maximum oil resistance

Reinforcement - Dual high tensile wire helix embedded between layers of textile cords

Cover - Specially formulated oil resistant rubber to remain flexible in low temperatures. Blue corrugated cover with red lay line

Branding - Red stripe "POLAR MAXX LOW TEMP TANK TRUCK 150 P.S.I."

### Temperature Range:

-51°C to +82°C (-60°F to +180°F)

### Standard Lengths:

100ft cut to multiples of 5ft

Parts No.	I.D. Inches	O.D. Inches	Bend Radius Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
TT-LT-1	1	1.42	4	150	0.58
TT-LT-1.5	1-1/2	1.93	6	150	0.89
TT-LT-2	2	2.52	7	150	1.15
TT-LT-3	3	3.55	9	150	1.92
TT-LT-4	4	4.68	13	150	3.20

