



PET

## PETROLEUM DISCHARGE

### Application:

For handling a wide range of petroleum based products, including gasoline, and a number of chemical solutions. Also ideal for air service with oil laden, and heated air. Maximum aromatic content 50%.

### Construction:

Tube - Black heat and oil resistant Nitrile  
Reinforcement - Multiple layers of synthetic textile cords with static wire  
Cover - Red, heat, oil and weather resistant neoprene  
Branding - "Petroleum Discharge Hose 150PSI"

### Temperature Range:

-35°C to +82°C (-31°F to +180°F)

### Standard Lengths:

50ft / 100ft

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
PET-.75	3/4	1.10	150	0.30
PET-1	1	1.14	150	0.44
PET-1.25	1-1/4	1.65	150	0.53
PET-1.5	1-1/2	1.89	150	0.70
PET-2	2	2.48	150	0.90
PET-2.5	2-1/2	2.99	150	1.22
PET-3	3	3.49	150	1.45
PET-4	4	4.56	150	1.89



DROP

## DROP HOSE

### Application:

A lightweight, flexible drop hose for gasoline delivery service. Will handle the same range of products as Tank Truck hose. Suitable for full vacuum. Maximum aromatic content 50%.

### Construction:

Tube - Black oil and gasoline resistant nitrile rubber  
Reinforcement - A double wire helix embedded between two layers of textile cords  
Cover - Corrugated red neoprene which is abrasion, oil and gasoline resistant  
Branding - Unbranded

### Temperature Range:

-35°C to +82°C (-31°F to +180°F)

### Standard Lengths:

100ft cut to multiples of 5ft

Parts No.	I.D. Inches	O.D. Inches	Bend Radius Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
DROP-2	2	2.44	8	75	1.23
DROP-3	3	3.50	12	75	1.92
DROP-4	4	4.50	18	75	2.88