

SKIRTBOARD RUBBER 55 DUROMETER

COMMERCIAL RECYCLED RUBBER

ISO/ASTM DESIGNATION = SBR



Physical Characteristics:

Tensile: 500 PSI

Elongation: 300%

Hardness: 55 SHORE "A" +/-5

Temperature Range: -20°C to 80°C (-4°F to 176°F)

Tolerance on Width: +/- .3937"

Parts No.	Gauge x Width	Length	Wt. Per LN ft.	Colour	Finish
SKBI55-.25-4	1/4" X 4"	50FT	0.63	Black	Smooth
SKBI55-.25-5	1/4" X 5"	50FT	0.79	Black	Smooth
SKBI55-.25-6	1/4" X 6"	50FT	0.95	Black	Smooth
SKBI55-.25-8	1/4" X 8"	50FT	1.25	Black	Smooth
SKBI55-.25-12	1/4" X 12"	50FT	1.89	Black	Smooth
SKBI55-.375-4	3/8" X 4"	50FT	0.94	Black	Smooth
SKBI55-.375-5	3/8" X 5"	50FT	1.17	Black	Smooth
SKBI55-.375-6	3/8" X 6"	50FT	1.41	Black	Smooth
SKBI55-.375-8	3/8" X 8"	50FT	1.88	Black	Smooth
SKBI55-.375-12	3/8" X 12"	50FT	2.83	Black	Smooth
SKBI55-.5-4	1/2" X 4"	50FT	1.25	Black	Smooth
SKBI55-.5-5	1/2" X 5"	50FT	1.57	Black	Smooth
SKBI55-.5-6	1/2" X 6"	50FT	1.88	Black	Smooth
SKBI55-.5-8	1/2" X 8"	50FT	2.51	Black	Smooth
SKBI55-.5-12	1/2" X 12"	50FT	3.77	Black	Smooth
SKBI55-.75-6	3/4" X 6"	50FT	2.84	Black	Smooth
SKBI55-.75-12	3/4" X 12"	50FT	5.66	Black	Smooth
SKBI55-1-3	1" X 3"	50FT	1.89	Black	Smooth
SKBI55-1-6	1" X 6"	50FT	3.77	Black	Smooth
SKBI55-1-8	1" X 8"	50FT	5.02	Black	Smooth

NOTE: Cut to width Skirtboard Rubber is designed for use as skirting on conveyor belt systems. A great cost saving item.