

## RED SHEET PACKING RUBBER SMOOTH 80 DUROMETER

ISO/ASTM DESIGNATION = SBR



### Physical Characteristics:

Tensile: 500 PSI

Elongation: 250%

Hardness: 80 SHORE "A" +/- 5

Temperature Range: -20°C to 80°C (-4°F to 176°F)

Parts No.	Gauge x Width	Length	Wt. Per SF lbs.	Colour	Finish
RSPSI-.063-36	1/16" X 36"	100FT	0.56	Red	Smooth
RSPSI-.063-48	1/16" X 48"	100FT	0.56	Red	Smooth
RSPSI-.094-48	3/32" X 48"	66FT	0.84	Red	Smooth
RSPSI-.125-36	1/8" X 36"	66FT	1.11	Red	Smooth
RSPSI-.125-48	1/8" X 48"	66FT	1.11	Red	Smooth
RSPSI-.188-36	3/16" X 36"	66FT	1.67	Red	Smooth
RSPSI-.188-48	3/16" X 48"	66FT	1.67	Red	Smooth
RSPSI-.25-36	1/4" X 36"	33FT	2.23	Red	Smooth
RSPSI-.25-48	1/4" X 48"	33FT	2.23	Red	Smooth

**NOTE:** An economical red sheet with a smooth finish used in low-pressure applications with no oil resistant requirements. This rubber is also ideal for gaskets and other sheet applications where a recognizable red colour is required.