Sheet Rubber & Matting

REDSTAR RUBBER 40 DUROMETER

ISO/ASTM DESIGNATION = NR



Physical Characteristics:

Tensile: 2300 PSI Elongation: 600%

Hardness: 40 SHORE "A" +/-5

Temperature Range: -40°C to 70°C (-40°F to 158°F)

			Wt. Per		
Parts No.	Gauge x Width	Length	SF lbs.	Colour	Finish
DURA063-48	1/16" X 48"	100FT	0.34	Red	Smooth
DURA125-48	1/8" X 48"	66FT	0.68	Red	Smooth
DURA25-48	1/4" X 48"	50FT	1.36	Red	Smooth
DURA375-48	3/8" X 48"	50FT	2.02	Red	Smooth
DURA5-48	1/2" X 48"	50FT	2.71	Red	Smooth
	DURA063-48 DURA125-48 DURA25-48 DURA375-48	DURA063-48 1/16" X 48" DURA125-48 1/8" X 48" DURA25-48 1/4" X 48" DURA375-48 3/8" X 48"	DURA063-48 1/16" X 48" 100FT DURA125-48 1/8" X 48" 66FT DURA25-48 1/4" X 48" 50FT DURA375-48 3/8" X 48" 50FT	Parts No. Gauge x Width Length SF lbs. DURA063-48 1/16" X 48" 100FT 0.34 DURA125-48 1/8" X 48" 66FT 0.68 DURA25-48 1/4" X 48" 50FT 1.36 DURA375-48 3/8" X 48" 50FT 2.02	Parts No. Gauge x Width Length SF lbs. Colour DURA063-48 1/16" X 48" 100FT 0.34 Red DURA125-48 1/8" X 48" 66FT 0.68 Red DURA25-48 1/4" X 48" 50FT 1.36 Red DURA375-48 3/8" X 48" 50FT 2.02 Red

NOTE: A soft long wearing non-marking natural rubber sheet that comes in red. This product has excellent abrasion and tear resistance. It also has superior resilience, tensile and elongation characteristics. Red-Star is excellent on all steel surfaces against abrasion. Red-Star is not designed for outdoor or oil resistant applications.

Eastern Canada: 1-905-670-5700 Western Canada: 1-604-472-1200