



PS

PAINT SPRAY

Application:

Paint spray applications involving most common solvents such as lacquer thinners, turpentine and Duco.

Construction:

Tube - Co-extruded blue LLDPE / rubber blend

Reinforcement - High tensile synthetic textile

Cover - Black smooth oil & abrasion resistant synthetic rubber

Temperature Range:

-40°C to +52°C (-40°F to +125°F)

Standard Lengths:

1/4" - 1/2" 25ft multiples & 500ft reels
3/4" 25ft multiples & 300ft reels

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
PS-.25	1/4	0.500	175	0.072
PS-.375	3/8	0.690	175	0.120
PS-.5	1/2	0.875	175	0.186
PS-.75	3/4	1.190	150	0.283



EVA

EVA WEED SPRAY

Application:

Used for all low pressure agricultural spray applications, including Monsanto LASSO and anhydrous ammonia.

Construction:

Tube - Clear EVA (Ethylene vinyl acetate)

Reinforcement - Multiple layers of polyester yarn

Cover - Clear abrasion & weather resistant EVA

Temperature Range:

-23°C to +65°C (-10°F to +150°F)

Standard Lengths:

25ft multiples & 300ft coils

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
EVA-.375	3/8	0.59	300	0.07
EVA-.5	1/2	0.72	250	0.09
EVA-.75	3/4	0.97	150	0.13
EVA-1	1	1.31	150	0.24