



PWDN

PAPERMILL WASHDOWN WITH BUILT-ON-NOZZLE

Application:

Suitable for hot or cold water washdown service in papermills. Hose incorporates an integral built-on smooth tapered rubber nozzle.

Construction:

Tube - Black synthetic heat resistant rubber
Reinforcement - Multiple spirals of moisture resistant synthetic yarn
Cover - Green abrasion resistant rubber

Temperature Range:

-35°C to +95°C (-31°F to +203°F)

Standard Lengths:

50ft

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. 50ft. Length c/w Nozzle
PWDN-.75	3/4	1.14	150	37
PWDN-1	1	1.41	150	46
PWDN-1.25	1-1/4	1.73	150	72
PWDN-1.5	1-1/2	2.04	150	93



GP

GREEN PACKERS WASHDOWN

Application:

For washdown service in packing houses, breweries, dairies, fish processing plants, and canneries. Suitable for hot water to 95°C (203°F). Not recommended for pure steam service. Mandrel built.

Construction:

Tube - Black synthetic compounded for heat resistance
Reinforcement - Two layers of synthetic yarns
Cover - Green cover. Resistant to lactic acid, animal & butter fats, heat weathering and abrasion

Temperature Range:

-40°C to +95°C (-40°F to +203°F)

Standard Lengths:

50ft / 100ft

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
GP-.5	1/2	0.91	250	0.28
GP-.75	3/4	1.25	250	0.40
GP-1	1	1.46	250	0.53