

Washdown Hose

Washdown Hose

HWWU



HOT WATER WASH UP

Application:

For general clean-up and hot water washdown service up to 93°C (200°F) at 50 PSI in dairies, meat packing houses, creameries, food processing and bottling plants. Not suitable for steam service.

Construction:

Tube - Black heat resistant EPDM
Reinforcement - Spiral polyester yarn
Cover - White smooth EPDM

Temperature Range:

-40°C to +82°C (-40°F to +180°F)

Standard Lengths:

25ft / 700ft

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
HWWU-.5	1/2	0.94	250	0.30
HWWU-.75	3/4	1.25	200	0.51

SHW



SUPER HOT WATER WASH UP

Application:

For general clean-up and hot water washdown service in dairies, meat packing houses, creameries, food processing and bottling plants. The use of premium materials gives longer service life under high temperature use. Not suitable for steam service. Mandrel built.

Construction:

Tube - White FDA compound heat resistant synthetic rubber
Reinforcement - Two layers of synthetic yarns. Fungus and mould resistant
Cover - White synthetic rubber, heat and abrasion resistant

Temperature Range:

-32°C to +82°C (-25°F to +220°F)

Standard Lengths:

25ft / 50ft / 75ft / 100ft

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
SHW-.5	1/2	0.94	150	0.33
SHW-.75	3/4	1.23	150	0.50
SHW-1	1	1.52	150	0.70

