

Water Discharge Hose

Water Discharge Hose



CWDT

CONTRACTORS WATER DISCHARGE LONG LENGTH

Application:

For use on construction sites and general water service.

Construction:

Tube - Black EPDM
Reinforcement - Multiple spirals of synthetic yarn
Cover - Black smooth EPDM

Temperature Range:

-40°C to +93°C (-40°F to +200°F)

Standard Lengths:

1/2" to 1" 25ft multiples & 700ft reels
1-1/4" 25ft multiples & 550ft reels
1-1/2" 25ft multiples & 400ft reels

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
CWDT-.25-200	1/4	.50	200	0.08
CWDT-.313-300	5/16	.63	300	0.13
CWDT-.375-200	3/8	.69	200	0.15
CWDT-.375-300	3/8	.72	300	0.17
CWDT-.5-150	1/2	.81	150	0.19
CWDT-.5-300	1/2	.88	300	0.24
CWDT-.625-150	5/8	.94	150	0.23
CWDT-.625-200	5/8	1.00	200	0.29
CWDT-.75-150	3/4	1.13	150	0.33
CWDT-.75-300	3/4	1.16	300	0.40
CWDT-1-150	1	1.43	150	0.41
CWDT-1-200	1	1.43	200	0.49
CWDT-1.25-200	1-1/4	1.78	200	0.79
CWDT-1.5-200	1-1/2	2.03	200	0.90



CHAL-BLK

CHALLENGER WATER DISCHARGE HOSE

Application:

An economical water discharge hose used in a wide range of water applications. Due to Challenger's rubber construction, this hose is flexible and lightweight for ease of use.

Construction:

Tube - Black blended rubber
Reinforcement - High tensile synthetic yarn
Cover - Smooth black abrasion resistant rubber

Temperature Range:

-20°C to +82°C (-4°F to +180°F)

Standard Lengths:

25ft multiples & 500ft reels.

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
CHAL-BLK-.5-150	1/2	0.83	150	0.26
CHAL-BLK-.625-150	5/8	0.94	150	0.33
CHAL-BLK-.75-150	3/4	1.14	150	0.44
CHAL-BLK-1-150	1	1.40	150	0.55

