

Water Discharge Hose

Water Discharge Hose



CWD

FLOW MAXX WATER DISCHARGE MANDREL MADE

Application:

For use on construction sites and general water service.

Construction:

Tube - Black EPDM rubber

Reinforcement - Multiple spirals of synthetic yarn

Cover - Black EPDM rubber

Branding - Yellow Stripe "FLOW MAXX EPDM WATER DISCHARGE HOSE"

Temperature Range:

-32°C to +82°C (-25°F to +180°F)

Standard Lengths:

1-1/4" to 10" 50ft / 100ft
12" 50ft

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
CWD-1.25	1-1/4	1.54	100	0.44
CWD-1.5	1-1/2	1.77	100	0.56
CWD-2	2	2.28	100	0.70
CWD-2.5	2-1/2	2.72	100	1.03
CWD-3	3	3.27	85	1.20
CWD-4	4	4.29	85	1.60
CWD-5	5	5.39	85	2.03
CWD-6	6	6.34	75	2.60
CWD-8	8	8.39	75	3.50
CWD-10	10	10.50	75	4.80
CWD-12	12	12.51	75	5.89



PWD

PREMIUM WATER DISCHARGE

Application:

A heavy duty hose for water discharge service.

Construction:

Tube - Black synthetic rubber - oil mist resistant

Reinforcement - Multiple spirals of synthetic yarn

Cover - Green abrasion and cut resistant synthetic rubber

Branding - Unbranded

Temperature Range:

-32°C to +82°C (-25°F to +180°F)

Standard Lengths:

25ft / 50ft / 100ft

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
PWD-1.25	1-1/4	1.65	200	0.65
PWD-1.5	1-1/2	1.89	200	0.72
PWD-2	2	2.48	150	1.16
PWD-2.5	2-1/2	3.07	150	1.75
PWD-3	3	3.59	150	2.07
PWD-4	4	4.58	150	2.67
PWD-5	5	5.63	150	3.85
PWD-6	6	6.69	150	5.07
PWD-8	8	8.87	75	7.90
PWD-10	10	10.99	75	9.50
PWD-12	12	13.12	75	11.20

