

# Water Suction Hose

Water Suction Hose



TIGER

## TIGER TAIL PVC SUCTION

### Application:

Improved double helix design allows for superior flexibility and durability even in sub-zero temperatures. Designed to provide maximum abrasion protection for sewer jetting hose, expensive camera and utility inspection equipment. Recommended for Light Bulk Material Handling Applications.

### Construction:

Tube - Smooth interior increases flow efficiency even at sharp bends

Cover - Black and yellow tough abrasion resistant ribs

### Temperature Range:

-40°C to +60°C (-40°F to +140°F)

### Standard Lengths:

1-1/2" - 4" 25ft and 50ft lengths

Non-standard lengths - made to order

\* Price per foot includes Poly-welded leak proof cuffs each end.

Parts No.	I.D. Inches	Weight (lbs./ft)	Positive. PSI	Negative IN.HG	Bend Radius Inches
TIGER-1.5	1-1/2	.35	26	29	3.75
TIGER-2	2	.65	17	29	5.00
TIGER-3	3	1.20	12	29	8.00
TIGER-4	4	1.60	7	29	9.50



220RS

## 220RS RUBBER WATER SUCTION

### Application:

Lightweight and kink resistant for rough construction applications. Suitable for full vacuum.

### Construction:

Tube - Smooth black synthetic

Reinforcement - Rigid PVC helix

Cover - Smooth black abrasion resistant synthetic rubber

### Temperature Range:

-40°C to +60°C (-40°F to +140°F)

### Standard Lengths:

1-1/2" - 4" 100ft cut to multiples of 5ft at no charge

6" 100ft cut to multiples of 10ft at no charge

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
220RS-1.5	1-1/2	1.78	50	0.50
220RS-2	2	2.38	50	0.74
220RS-2.5	2-1/2	2.92	50	1.01
220RS-3	3	3.41	43	1.21
220RS-4	4	4.50	38	2.01
220RS-6	6	6.67	23	3.37

