



OXYTUBE SINGLE LINE WELDING - OXYGEN HOSE - GRADE R

Application:

For use with all fuel gases, where a flame and oil resistant tube and cover is required

Construction:

Tube - Black EPDM rubber
Reinforcement - Multi-spiral synthetic yarn
Cover - Green corrugated EPDM pin pricked

Standard Lengths:

Multiples of 25ft, 700ft reels and coupled assemblies

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
OXY-.188	3/16	0.44	200	0.08
OXY-.25	1/4	0.59	200	0.14
OXY-.313	5/16	0.66	200	0.16
OXY-.375	3/8	0.72	200	0.18

Coupled Assembly - Female welding stem and nut type "B" each end.

Coupled assemblies part numbers are OXY-SIZE-LENGTH
i.e. for 1/4" Oxygen Single Line Grade R Assembly x 25ft long
Part number = OXY-.25-25



OXYTUBE SINGLE LINE WELDING - ACETYLENE HOSE - GRADE R

Application:

For use with all fuel gases, where a flame and oil resistant tube and cover is required

Construction:

Tube - Black EPDM rubber
Reinforcement - Multi-spiral synthetic yarn
Cover - Red corrugated EPDM pin pricked

Standard Lengths:

Multiples of 25ft, 700ft reels and coupled assemblies

Parts No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Approx. Wt. Per. Ft. Lbs.
ACE-.188	3/16	0.44	200	0.08
ACE-.25	1/4	0.59	200	0.14
ACE-.313	5/16	0.66	200	0.16
ACE-.375	3/8	0.72	200	0.18

Coupled Assembly - Female welding stem and nut type "B" each end.

Coupled assemblies part numbers are ACE-SIZE-LENGTH
i.e. for 1/4" Acetylene Grade R Assembly x 25ft long
Part number = ACE-.25-25